

Direct Spark Ignition

24VAC & 120VAC

DXML Series

MINILITER

FEATURES:

- Natural or LP Gas Equipment
- Potted or with Integral Stand-Offs
- Rugged Design
- Easy Mounting
- Compact Size



APPLICATIONS:

- Barbecue Grills
- Fire Places
- Construction Heaters
- Space Heaters

DESCRIPTION

The model DXML above is a 24VAC or 120VAC Direct Spark ignition control. The small compact design provides a manual spark to ignite various gas fired appliances. The rugged construction ensures a safe and efficient operation.

Simple economical design makes it the right choice for any manual gas fired direct spark appliance and works with both natural and LP gas.

APPROVALS

Designed to ANSI Z21.20 Standards

Specifications

INPUT VOLTAGE	- 18-30VAC 50/60 Hz (Class 2 Transformer) or - 102-138VAC 50/60 Hz
CURRENT DRAW MAIN VALVE	2.0A @ 24VAC or 120VAC
INPUT CURRENT DRAIN	300 mA @ 24VAC, 350 mA @120VAC
VALVE CONTACT RATING	2.0A @ 24VAC, 1.5A@ 120VAC
OPERATING TEMPERATURE	-40F to 175F, -40C to +80C
TYPES OF GASES	Natural, LP, or Manufactured
SPARK RATE	50/60 Hz (Line Frequency)
ENCLOSURE	Potted or Integral Stand Offs
MOISTURE RESISTANCE	CONFORMAL COATED OR POTTED TO 95% R.H. AVOID DIRECT EXPOSURE TO WATER
WEIGHT	2 oz

WARNING

DISCONNECT THE POWER SUPPLY BEFORE MAKING WIRING CONNECTIONS TO PREVENT ELECTRICAL SHOCK OR EQUIPMENT DAMAGE.

**EXPLOSION HAZARD.
CAN CAUSE INJURY OR EQUIPMENT DAMAGE.**

Only trained professional gas appliance service technicians should install and check out this control.

Main Offices/Warehouse:



3267 Grapevine Street
Mira Loma, CA 91752
TEL: 951-360-5537
FAX: 951-360-5329

Web: www.bennitech.com